# **Focus Report**

New Chemicals Program Case Number: L-19-0033



Focus Date: 12/20/2018			
Report Status: Complete			
Focus Chair: Jeff Bauer			
Contractor:			
Consolidated Set:			
I. Notice Information			
Submitter:			
CAS Number: None			
Chemical Name:			I
Use: Intended use:			
Patents (same use): None.			
Other Uses: Analogues (other uses):			
Analogues (same + other uses): None. Patents (other use): None.			
Bind: ☑	impo	rts: ☑	
Manufacture: □	PV-m	aax(kg/yr):	
II. SAT Results			
Health Rating 1: 2		Health Rating 2:	
Occupational Rating: 2-3C		Non Occupational Rating: 2	
Ecotox Rating 2: 3		Environmental Rating: 1	
Health Rating Comment 1:			
Health Rating Comment 2:			
Persistence 1: 1	Bioaccumulation 1:	1	Toxicity 1:
PBT Comments 1: PMN			
Persistence 2: 3	Bioaccumulation 2:	*	Toxicity 2:
PBT Comments 2: Deg Pdt	, B*(high)		
III. OTHER FACTORS			
Categories			

Health Chemical Category:

```
Ecotox SARs: Carbamate Esters
Ecotox SAR Class: carbamate esters-perfluoro
Ecotox TSCA New Chemical Category: None
Related Cases / Regulatory History
Health Related Cases
Ecotox Related Cases: Same As:
Regulatory History:
MSDS/Label Information
MSDS: Y
                                                          Label: Y
Exposure Based Information
Exposure Based Review (Chemistry): N
Exposure Based Review (Health):
Exposure Based Review (Ecotox): N
Exposure Based Review (Occupational):
Exposure Based Review (Non-Occupational):
Exposure Based Review (Environmental):
IV. Summary of SAT Assessment
Fate
Fate Summary: L-19-0033
FATE:
Solid with MP = 71-73 °C (M)
S < 0.001 \text{ mg/L} at 25 °C (E)
VP < 1.0E-6 torr at 25 °C (E)
BP = Dec. > 200 \, ^{\circ}C \, (M)
H \le 1.00E-8 (E)
POTW removal (%) = 90 via sorption and biodeg; Deg Pdt
Time for complete ultimate aerobic biodeg = PMN > mo; Deg Pdt
Sorption to soils/sediments = PMN strong; Deg Pdt
PBT Potential: PMN P1B1; Deg Pdt
                                          P3B*(high)
FATE: Migration to ground water = PMN slow; Deg Pdt
                                                             rapid
Bioconcentration factor to be put into E-FAST: Deg Pdt
```

PMN Material:

Overall wastewater treatment removal is 90% via sorption and biodegradation.

Sorption to sludge is strong based on data for fluorinated chemicals.

Air Stripping (Volatilization to air) is low based on data for fluorinated chemicals.

Removal by biodegradation in wastewater treatment is high based on data for fluorinated chemicals.

Destruction of the substance in wastewater treatment is partial based on data for fluorinated chemicals.

The aerobic primary aquatic biodegradation half-life is less than two months based on data for fluorinated chemicals. Primary degradation of the alkyl chain and the amide is expected.

The aerobic ultimate aquatic biodegradation half-life is greater than six months based on data for fluorinated chemicals.

The anaerobic primary aquatic biodegradation half-life is two to six months based on data for fluorinated chemicals.

The anaerobic ultimate aquatic biodegradation half-life is greater than six months based on the aerobic biodegradation half-

life. The anaerobic biodegradation half-life is projected to be greater than or equal to the aerobic biodegradation half-life.

Sorption to soil and sediment is strong based on data for fluorinated chemicals.

Migration to groundwater is slow based on data for fluorinated chemicals.

PMN Material:

Not Persistent (P1) based on the estimated aerobic primary biodegradation half-life.

Low Bioaccumulation (B1) based on data for fluorinated chemicals.

**Degradation Product** 

Overall wastewater treatment removal is 0% based on low biodegradability, low sorption and low stripping.

Sorption to sludge is low based on data for fluorinated chemicals.

Air Stripping (Volatilization to air) is low based on data for fluorinated chemicals.

Removal by biodegradation in wastewater treatment is negligible based on data for fluorinated chemicals.

The aerobic aquatic biodegradation half-life is greater than six months based on data for fluorinated chemicals.

The anaerobic aquatic biodegradation half-life is greater than six months based on the aerobic biodegradation half-life. The anaerobic biodegradation half-life is projected to be greater than or equal to the aerobic biodegradation half-life.

Sorption to soil and sediment is low based on data for fluorinated chemicals.

Migration to groundwater is rapid based on data for fluorinated chemicals.

Degradation Product

Very Persistent (P3) based on the estimated aerobic and anaerobic biodegradation half-lives.

Bioaccumulation (B\*-high) based on data for fluorinated chemicals.

Bioconcentration/Bioaccumulation factor to be put into E-Fast: 93.

### Ecotox

**Ecotox Values** 

Fish 96-h LC50: 2.3(P)

Daphnid 48-h LC50: 8.3(P)

Green Algae 96-h EC50: 3.8(P)

Fish Chronic Value: 0.023(P)

**Daphnid Chronic Value:** 3.1(P)

**Green Algae Chronic Value:** 1.7(P)

**Ecotox Value Comments:** Predictions are based on QSARs for carbamate esters (ECOSAR V2.0); MW Log Kow = 13.35 (P); with a MP = 71-73C (M); S = 2.6E-10 mg/L (P); effective concentrations based on 100% active ingredients and mean measured concentrations; hardness <150 mg/L as CaCO3; and TOC <2.0 mg/L.

#### **Ecotox Factors**

Acute Aquatic Factors: Most Sensitive Endpoint: 2300 Assessment Factor: 5 CoC: 460
Chronic Aquatic Factors: Most Sensitive Endpoint: 23 Assessment Factor: 10 CoC: 2.3

Comments: Environmental Hazard: Environmental hazard is relevant to whether a new chemical substance is likely to present unreasonable risk because the significance of the risk is dependent upon both the hazard (or toxicity) of the chemical substance and the extent of exposure to the substance. EPA determined environmental hazard for this new chemical substance based on an analogous chemical of the degradation product. Acute toxicity values estimated for fish, aquatic invertebrates, and algae are 2.3 mg/L, 8.3 mg/L, and 3.8 mg/L, respectively. Chronic toxicity values estimated for fish, aquatic invertebrates, and algae are 0.023 mg/L (acute to chronic ratio (ACR)), 3.1 mg/L, and 1.7 mg/L, respectively. These toxicity values indicate that the new chemical substance is expected to have high environmental hazard. Application of assessment factors of 4 and 10

to acute and chronic toxicity values, respectively, results in acute and chronic concentrations of concern of 0.46~mg/L (460~ppb) and 0.0023~mg/L (2.3~ppb), respectively.

Environmental Risk: Risks to the environment were evaluated by comparing estimated surface water concentrations with the acute and chronic concentrations of concern. Risks to the environment were not identified due to releases to water that did not exceed the acute COC or the chronic COC.

## V. Summary of Exposure/Releases

### **Engineering Summary Release**

Exposures/Releases	Release	Release	
Scenario	PROC: Disposal	USE 1:	USE 1:
Site			
Media	Landfill	Air	Landfill
Descriptor A	Output 2	Output 2	Output 2
Quantity A (Release=kg/site/day; Exposure=mg/day)			
Frequency A (day/year)			
Descriptor B			
Quantity B (Release=kg/site/day; Exposure=mg/day)			
Frequency B (day/year)			
From			
Workers			
ExposureType			

Exposures/Releases	Release	Release	
Scenario	USE 1:	USE 1:	USE 1:
Site			
Media	Landfill	Water or Air	Inhalatio
Descriptor A	Output 2	Output 2	Worst Case
Quantity A (Release=kg/site/day; Exposure=mg/day)			
Frequency A (day/year)			
Descriptor B			Typical

Exposures/Releases	Release	Release	
Quantity B			
(Release=kg/site/day;			
Exposure=mg/day)			
Frequency			
B			
(day/year)			
From			
Workers			
ExposureType			Vapor

Exposures/Releases	Exposure	Release	
Scenario	USE 1:	USE 2:	USE 2: Recr
Site			
Media	Inhalation	Air	Landfill
Descriptor A	Inhalable	Output 2	Output 2
Quantity A (Release=kg/site/day; Exposure=mg/day)			
Frequency A (day/year)			
Descriptor B	Respirable		
Quantity B (Release=kg/site/day; Exposure=mg/day)			
Frequency B (day/year)			
From	Worker Exposure to Particulates During Application		
Workers			
ExposureType	Particulate		

Exposures/Releases	Release	Release	
Scenario	USE	USE 2:	USE
	2:		
Site			
Media	Landfill	Water	Inhal
		or Air	
Descriptor	Output 2	Output 2	Wors
A	_	_	Case
Quantity A			
(Release=kg/site/day;			
Exposure=mg/day)			
			<b>-</b>
I			

Exposures/Releases	Release	Release
Frequency		
A		
(day/year)		
Descriptor		Туріс
В		
Quantity B		
(Release=kg/site/day;		
Exposure=mg/day)		
Frequency		
В		
(day/year)		
From		
Workers		
ExposureType		Vapo

Exposures/Releases	Exposure	Release	
Scenario	USE 2:	USE 3	USE 3:
Site			
Media	Inhalation	Water or Air or Landfill	Landfill
Descriptor A	Inhalable Particulate	Output 2	High End
Quantity A (Release=kg/site/day; Exposure=mg/day)			
Frequency A (day/year)			
Descriptor B	Respirable Particulate		
Quantity B (Release=kg/site/day; Exposure=mg/day)			
Frequency B (day/year)			
From	Worker Exposure to Particulates During Application		
Workers			
ExposureType	Particulate		

Exposure	Expo
USE 3:	USE 3:
Dermal	Inhalation
High End	Spray Mist
	USE 3: Dermal

Exposures/Releases	Exposure	Expo
Quantity A (Release=kg/site/day; Exposure=mg/day)		
Frequency A (day/year)		
Descriptor B		
Quantity B (Release=kg/site/day; Exposure=mg/day)		
Frequency B (day/year)		
From		
Workers		
ExposureType	Liquid	Mist

### **Exposure Summary Release**

Chemical ID: L-19-0033

### Reviewer:

Exposure Scenario	Water					Land fill (non- sludge)	Sta	ıck	
Release Activity(ies) exposure Calculations	ADR mg/kg/day	g Water LADD mg/kg/day	Fish In ADR mg/kg/day	LADD mg/kg/day	7Q10cc ug/l	PDM Exceeded # Days	LADD mg/kg/day	ADR mg/kg/day	LAD mg/kg/
USE1:Max ADR	2.15e-6 2.15e-6	0.00e+0	3.21e-6	0.00e+0	1.00e-1	0.00e+0	0.00e+0	0.00e+0	
USE1:PDM	0.00e+0	0.00e+0	0.00e+0	0.00e+0	1.00e-1	0.00e+0	0.00e+0	0.00e+0	
USE1:Max LADD	0.00e+0	6.56e-9	0.00e+0	4.40e <b>-</b> 9	0.00e+0	0.00e+0	2.05e-6	0.00e+0	
USE2:Max ADR	3.12e-5 3.12e-5	0.00e+0	4.67e-5	0.00e+0	1.51e+0	0.00e+0	0.00e+0	0.00e+0	
USE2:Max LADD	0.00e+0	6.51e-9	0.00e+0	4.37e <b>-</b> 9	0.00e+0	0.00e+0	1.91e-6	0.00e+0	
USE3:Max ADR	5.66e-4 5.66e-4	0.00e+0	8.47e-4	0.00e+0	2.74e+1	0.00e+0	0.00e+0	0.00e+0	
USE3:Max LADD	0.00e+0	1.97e-7	0.00e+0	1.32e-7	0.00e+0	0.00e+0	6.23e-8	0.00e+0	

- 1.Exposure scenario titles consist of release activity followed by exposure calculation abbreviation.
- 2.Release activities are from engineering report's Manufacturing (Mfg), Processing (Proc) and Use release activity labels. combined in one exposure scenario if their releases occur at same location.
- 3.Exposure calculations are Acute Dose Rate (ADR), Lifetime Average Daily Dose (LADD), and Probabilistic Dilution Mone, two, or all three exposure calculations per exposure scenario. CC is the aquatic concentration of concern.
- 4.This column displays concentration values for the 7Q10 streamflow, which is defined as the average daily streamflow of of lowest flow within a ten year period.

Result Table : Exposure Based(XB)/Persistent (P2B2) Criteria

Parameter	Exp Based	Persistent
Drinking(Surface) Water Dose (mg/kg/day)		

Parameter	Exp Based	Persistent
Fish Ingestion Dose (mg/kg/day)		
Inhalation Dose (mg/kg/day)		
Groundwater Dose (mg/kg/day)		
Surface Water Release After Treatment (kg/yr)		
Total Release After Treatment (kg/yr)		
Consumer Use?		

#### VI. Focus Decision and Rationale

Regulatory Actions

Regulatory Decision: LVE Conditional Denial Decision Date: 12/20/2018

**Decision Type:** 

Rationale: L-19-0033 was conditionally denied based on risks to workers, the general population, consumers, and PBT concerns. This chemical substance has a PBT rating of a high P3B\*T2. The submitter should consider addressing fugitive and stack air releases, updating the SDS to include appropriate PPE (i.e., a NIOSH-certified respirator with an APF of 1,000). There is concern for lung effects based on analogy to chemicals with waterproofing properties. There is also concern for systemic and male reproductive toxicity based on acidic degradation to in the environment

Workers: Risks were not identified for workers via dermal (MOE = 23,529; benchmark MOE=23,000) exposure for systemic and male reproductive toxicity based on analogue data. Risks were identified for workers via inhalation for lung waterproofing based on structural alerts (MOE = 2.5, benchmark MOE=1000, Fold Factor = 408). Risks were identified for workers via inhalation exposure for systemic and male reproductive toxicity based on analogue data. (MOE=364; benchmark MOE=23,000, Fold Factor = 63). Risks would be mitigated if exposures can be controlled by the use of appropriate PPE, including a respirator of APF = 1000.

General Population: Risks were identified for general population via stack and fugitive air inhalation for lung waterproofing based on structural alerts (MOE = 2.5stack, MOE=568fugitive, benchmark MOE=1000). Risks were identified for the general population via stack air inhalation for systemic and male reproductive toxicity based on analogue data (MOE=5319; benchmark MOE=23,000). Risks were not identified for the general population via drinking water, fish ingestion, or fugitive air inhalation (MOEs => 74,940; benchmark MOE=23,000) for systemic and male reproductive toxicity based on analogue data. Consumers: Risks were identified for consumers via inhalation (MOE = 3.1; benchmark MOE=23,000) exposure for lung waterproofing based on structural alerts. Risks were not identified for consumers via dermal exposure (MOEdermal = 7,246,377; benchmark MOE = 100) for systemic and male reproductive toxicity. Risks were identified for consumers via inhalation exposure (MOEinhalation = 1307; benchmark MOE=23,000) for systemic and male reproductive toxicity. Assumptions and Uncertainties: Absorption of the LVE is based on pchem. Metabolism is assumed to be important and is expected to degrade to during digestion. There are no measured data on the LVE substance itself. Health effects are based on analogue data. The evaluation of the LVE is based on presumed metabolite/degradant. Ecotoxicity hazard is estimated to be high based on QSAR predictions for carbamate esters (ECOSAR V2.0). Risks to the environment were not identified due to releases to water that did not exceed the acute COC or the chronic COC. This LVE is import only, was bound and assessed at

COC: Acute: 460 µg/L, Chronic: 2.3 µg/L

Summary of Exposures and Releases

Proc

days/yr, workers

Inhalation: Negligible (VP < 0.001 torr)

Dermal: Not expected

Releases via Landfill:

Fate Releases to Air

Stacked Air: LADD: 1.25E-05 mg/kg/day

Use1 sites, days/yr, workers Inhalation (Vapor): Typical: mg/day, Worst Case: mg/day Inhalation (Particulate): Respirable: mg/day, Total: mg/day Dermal: Not expected
Releases to Water: Or Air Releases to Air: Releases via Incineration: Or Landfill Releases via Incineration: Or Landfill
Fate Releases to Water (0% Removal) SWC: 3.96E-02 μg/L DW: LADD: 6.38E-09 mg/kg/day, ADR: 8.20E-07 mg/kg/day FI: LADD: 4.28E-09 mg/kg/day, ADR: 1.23E-06 mg/kg/day
Fate Releases to Air Stacked Air: LADD: 1.34E-06 mg/kg/day, ADR: 5.16E-05 mg/kg/day Fugitive Air: LADD: 1.48E-08 mg/kg/day, ADR: 1.43E-06 mg/kg/day
Fate Releases via Landfill LADD: 1.94E-06 mg/kg/day
Use2  sites, days/yr, workers Inhalation (Vapor): Typical: mg/day, Worst Case: mg/day Inhalation (Particulate): Respirable: mg/day, Total: mg/day Dermal: Not expected
Releases to Water: Or Air Releases to Air: Releases via Incineration: Or Landfill Releases via Incineration: Or Landfill
Fate Releases to Water (0% Removal) SWC: 1.51 $\mu$ g/L DW: LADD: 6.51E-09 mg/kg/day, ADR: 3.12E-05 mg/kg/day FI: LADD: 4.37E-09 mg/kg/day, ADR: 4.67E-05 mg/kg/day
Fate Releases to Air Stacked Air: LADD: 1.31E-06 mg/kg/day, ADR: 1.88E-03 mg/kg/day Fugitive Air: LADD: 1.11E-08 mg/kg/day, ADR: 4.01E-05 mg/kg/day
Fate Releases via Landfill LADD: 1.91E-06 mg/kg/day
Use3 sites, days/yr, workers Inhalation (Mist): Typical: mg/day, Worst Case: mg/day Dermal: mg/day (1.50% Liquid)
Releases to Water: Or Air or Incineration or Landfill Releases to Water: Or Incineration or Landfill

Fate Releases to Water (0% Removal)

SWC: 1.55 µg/L

DW: LADD: 6.67E-09 mg/kg/day, ADR: 3.20E-05 mg/kg/day FI: LADD: 4.48E-09 mg/kg/day, ADR: 4.79E-05 mg/kg/day

Fate Releases to Air

Stacked Air: LADD: 4.20E-08 mg/kg/day, ADR: 2.01E-06 mg/kg/day Fugitive Air: LADD: 3.38E-07 mg/kg/day, ADR: 3.26E-05 mg/kg/day

PDM

Fate Releases to Water (0% Removal)

SWC: 1.23 µg/L

DW: LADD: 1.99E-07 mg/kg/day, ADR: 2.54E-05 mg/kg/day FI: LADD: 1.34E-07 mg/kg/day, ADR: 3.80E-05 mg/kg/day

Fate Releases via Landfill LADD: 6.23E-08 mg/kg/day

CEM, User Defined

Inhalation: LADD: 4.59e-05 mg/kg/day, ADR: 7.65e-03 mg/kg/day Dermal: LADD: 8.31e-06 mg/kg/day, ADR: 1.38e-03 mg/kg/day

CEM, User Defined

Inhalation: LADD: 3.67e-04 mg/kg/day, ADR: 7.65e-03 mg/kg/day Dermal: LADD: 6.65e-05 mg/kg/day, ADR: 1.38e-03 mg/kg/day

### **P2 Rec Comments:**

**Testing** 

Health:

**Ecotox:** 

Fate:

**Final Recommendations**